



■ Rotating speed no higher than 1600RPM

--- Specifications / 规格参数 ---

| Capacity/量程                                | 10/20/30/50/100/200/300 NM            |                            |                     |
|--|---------------------------------------|----------------------------|---------------------|
| Rated Output/额定输出                          | 1.5 mV/V                              | Compensated Temp./温度补偿范围   | -10...+40°C         |
| Excitation/激励电压                            | 5~15V                                 | Operating Temp./工作温度范围     | -20...+60°C         |
| Zero Balance/零点输出                          | ±0.05mV/V                             | Temp. Shift Zero/零点温度漂移    | ±0.02% of R.O./°C   |
| Nonlinearity/非线性                           | ±0.25% of R.O.                        | Temp. Shift Span/灵敏度温度漂移   | ±0.02% of R.O./°C   |
| Hysteresis/滞后                              | ±0.25% of R.O.                        | Input Resistance/输入阻抗      | 750±50Ω             |
| Nonrepeatability/非重复性                      | ±0.2% of R.O.                         | Output Resistance/输出阻抗     | 700±5Ω              |
| Creep(10min)/蠕变                            | ±0.1% of R.O.                         | Insulation Resistance/绝缘阻抗 | >2000MΩ(50V)        |
| Safe Overload/安全过载                         | 120% of F.S.                          | Ingress Protection/防护等级    | IP40                |
| Ultimate Overload/极限过载                     | 150% of F.S.                          | Material of Element/弹性体材料  | Stainless steel/不锈钢 |
| Cable/导线                                   | Ø5*3000mm 4-core shielded cable/4芯屏蔽线 |                            |                     |
| R.O.=Rated Output/额定输出 F.S.=Full Scale/满量程 |                                       |                            |                     |

• Subject to change without notice / 如有更改,不另行通知