


Ordering Code

FHSR-1100kg

Model Capacity

Capacity(kg)	L	W	H	A	B	C	E	d	D	h	M
110/220/550/ 1100/1760	133.4	30.7	30.2	15.4	76.2	25.4	57.7	13	20.6	14.2	M12
2200	136.7	36.8	36.6	18.4	76.2	25.4	55.6	13	12.5	16.6	M12
4400	171.5	42.9	42.9	21.4	95.3	38.1	73.8	20.5	22.2	22.9	M20

Wiring Diagram



--- Specifications / 规格参数 ---

Capacity/量程	110/220/550/1100/1760/2200/4400 kg		
Rated Output 额定输出	1.94 mV/V	Compensated Temp. 温度补偿范围	-10...+40°C
Excitation 激励电压	3~15V	Operating Temp. 工作温度范围	-20...+65°C
Zero Balance 零点输出	±2% of R.O.	Temp. Shift Zero 零点温度漂移	±0.02% of R.O./10°C
Nonlinearity 非线性	±0.02% of R.O.	Temp. Shift Span 灵敏度温度漂移	±0.02% of R.O./10°C
Hysteresis 滞后	±0.02% of R.O.	Input Resistance 输入阻抗	390±30Ω
Nonrepeatability 非重复性	±0.02% of R.O.	Output Resistance 输出阻抗	352±3Ω
Creep(30min) 蠕变(30min)	±0.02% of R.O.	Insulation Resistance 绝缘阻抗	>5000MΩ(50V)
Safe Overload 安全过载	150% of F.S.	Ingress Protection 防护等级	IP68
Ultimate Overload 极限过载	200% of F.S.	Material of Element 弹性体材料	Stainless steel 不锈钢
Cable 导线	Ø5.4*3000mm 6-core shielded cable Ø5.4*3000mm 6芯屏蔽线		
R.O.=Rated Output/额定输出 F.S.=Full Scale/满量程			

• Subject to change without notice / 如有更改,不另行通知